

# DIN 8062 Standard PVC For Water Supply Pipe, Plastic Tube

## DIN 8062 Standard PVC Pipe Features

### **1、 PVC Pipe Features Description**

- a. Uniform wall thickness, stable sizes
  - b. Smooth pipe wall, low liquid resistance, high transfer efficiency
  - c. No blocking, no incrustation, good beautification effects
  - d. Easy to install, maintenance and repair, good seal effect
  - e. light, durable (30~50 years of life-expectancy)
- Property of UPVC Pipe

### **2. Excellent physical properties.**

UPVC pipes and fittings are corrosive resistance, high anti-impact strength, low fluid resistance

### **3.Long time service life**

The using time can be 40-50 years according to testing results provided by authority.

### **4.Light weight、 well practical and easy to install**

## **DIN 8062 Standard PVC Pipe Specification**

Details Specification :	
Items Name:	PVC Pipe
Material:	PVC-U
Diameter :	20mm ~ 800mm
Thickness:	2.0mm ~ 30.6mm
Color:	Gray PVC Pipe (normal )
Connection:	Glue or Gasket
Pressure:	PN25 ,PVC Pipe 2.5mpa
Standard:	DIN standard
Certification:	ISO14001,ISO9001,CE,SGS,COC

## DIN 8062 Standard PVC Pipe size

(DIN Standard,DIN8061,DIN 8062 )UPVC Pressure pipe for water supply PVC Pipe Drinking Water

(DIN Standard,DIN8061,DIN 8062 )UPVC Pressure pipe for water supply PVC Pipe Drinking Water							
nominal outside diamete r dn	S series SDR series and nominal pressure						
	S16	S12.5	S10	S8	S6.3	S5	S4
	SDR33	SDR2 6	SDR2 1	SDR17	SDR13. 6	SDR1 1	SDR9
	PN0.6 3	PN0.8	PN1.0	PN1.2 5	PN1.6	PN2.0	PN2. 5
	nominal wall thickness en						
20	-	-	-	-	-	2.0	2.3
25	-	-	-	-	2.0	2.3	2.8
32	-	-	-	2.0	2.4	2.9	3.6
40	-	-	2.0	2.4	3.0	3.7	4.5
50	-	2.0	2.4	3.0	3.7	4.6	5.6

63	2.0	2.5	3.0	3.8	4.7	5.8	7.1
75	2.3	2.9	3.6	4.5	5.6	6.9	8.4
90	2.8	3.5	4.3	5.4	6.7	8.2	10.1
110	2.7	3.4	4.2	5.3	6.6	8.1	10.0
125	3.1	3.9	4.8	6.0	7.4	9.2	11.4
140	3.5	4.3	5.4	6.7	8.3	10.3	12.7
160	4.0	4.9	6.2	7.7	9.5	11.8	14.6
180	4.4	5.5	6.9	8.6	10.7	13.3	16.4
200	4.9	6.2	7.7	9.6	11.9	14.7	18.2
225	5.5	6.9	8.6	10.8	13.4	16.6	-
250	6.2	7.7	9.6	11.9	14.8	18.4	-
280	6.9	8.6	10.7	13.4	16.6	20.6	-
315	7.7	9.7	12.1	15.0	18.7	23.2	-
355	8.7	10.9	13.6	16.9	21.1	26.1	-
400	9.8	12.3	15.3	19.1	23.7	29.4	-
450	11.0	13.8	17.2	21.5	26.7	33.1	-
500	12.3	15.3	19.1	23.9	29.7	36.8	-
560	13.7	17.2	21.4	26.7	-	-	-
630	15.4	19.3	24.1	30.0	-	-	-

710	17.4	21.8	27.2	-	-	-	-
800	19.6	24.5	30.6	-	-	-	-
900	22.0	27.6	-	-	-	-	-
1000	24.5	30.6	-	-	-	-	-
Note:Nominal wall thickness en will be subject to design stress $\sigma$ S12.5MPa							

## Huasheng Advantage

- 1.Delivery time: Within 45 days after receiving deposit;
- 2.Payment terms:30 T/T as deposit, balance payment on the copy of B/L. or L/C at sight;
- 3.MOQ: NO MOQ for fitting and normal sale pipe gray color;
- 4.Packing:Packed into polybags, then into woven bag;
- 5.Shipping Marks:To be decided.



Equipped with a professional factory, Huasheng Pipeline is one of the best manufacturers in China who can offer you DIN 8062 standard PVC for water supply pipe, plastic tube. We can also offer you the price list consultation of DIN 8062 standard PVC for water supply pipe, plastic tube, welcome to buy our customized products.